

SIEMENS Corporation

IPD-West Coast

4900 Old Ironsides Drive, M/S 503

P.O. Box 58075

Santa Clara, CA 95052-8075

PATENT APPLICATION
Attorney Docket No. : 99 P 7755 US**Express Mail Label No.: EM483534528US**
Date of Deposit: August 25, 1999**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE****THE ASSISTANT COMMISSIONER FOR PATENTS**
Washington, D.C. 20231**TRANSMITTAL LETTER FOR NEW APPLICATION**

Sir:

Transmitted herewith for filing is a(n) ☒ [X] Original patent application.
☒ [X] Utility ☐ [] Design ☐ [] Continuation-in-part application**INVENTOR(S): Thanh Tran, Hung B. Nguyen, and Frederick Kull****TITLE: COMMUNICATION NETWORK MANAGEMENT**

Enclosed are with this transmittal (submitted in duplicate) are the following :

- ☒ [X] 18 page specification.
☒ [X] 4 sheets of drawings ☐ [] formal drawings ☒ [x] informal drawings (one set)
☒ [X] The Declaration and Power of Attorney ☒ [x] signed ☐ [] unsigned
☒ [X] An Assignment Transmittal and Assignment to **SIEMENS INFORMATION AND COMMUNICATION NETWORKS, INC.** .
☒ [X] Information Disclosure Statement with PTO1449 and six (6) references.
☒ [X] Filing fee has been calculated as shown below (other than small entity):

For	Number Filed	Number Extra	Rate	Additional Fees
Total Claims	29 - 20	= 9	x \$ 18	\$ 162.00
Indep. Claims	3 - 3	= 0	x \$ 78	\$ 0.00
<input type="checkbox"/> [] First Presentation of a Multiple Dependent Claim			x \$260	\$ 0.00
			Basic filing Fee	\$760.00
			Total	\$922.00

Please charge my Deposit Account No. 19-2179 in the amount of \$ 922.00 . The Commissioner is hereby authorized to charge any fees that may be required, or credit any overpayment to Deposit Account No. 19-2179 pursuant to 37 CFR 1.25. A duplicate copy of this sheet is enclosed.

PLEASE MAIL CORRESPONDENCE TO:**Siemens Corporation**
Attn: Elsa Keller, Legal Administrator
Intellectual Property Department
186 Wood Avenue South
Iselin, NJ 08830

Respectfully submitted,

**Rosa S. Kim**
Reg. No.: 39,728
Date: August 25, 1999
Telephone: (408) 492-4956

Date of Deposit August 25, 1999

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

TITLE: Communication Network Management

Inventor #2: Hung B. Nguyen
Address: 2239 Wellington Drive, Milpitas, Ca 95035
Citizenship: U.S.

Inventor #3: Frederick Kull
Address: 695 Cypress Lane, Campbell, CA 95008
Citizenship: U.S.

DISCOUNTS

BACKGROUND OF THE INVENTION

FIELD OF THE INVENTION

The present invention relates to the field of telecommunications and, in particular, to a system for managing a telecommunications network.

DESCRIPTION OF THE RELATED ART

Telephony based communication networks typically include a variety of components or products that combine to provide communication services to multiple users. Traditionally, these networks utilize dedicated application programs for each of the network components to control configuration and management of the corresponding components. Dedicated PBX and phone mail applications, as examples, have provided the traditional method of managing a communication network that includes a PBX component and a phone mail component. Unfortunately, the performance of such systems during execution of routine system management tasks such as move, add, and change tasks is frequently unacceptable to the end user. As an example, when a user of the communication network moves within an organization, the various components of the network must be updated to reflect the user's new location. While traditional configuration and management applications are adequate to control a specific product or component, they are typically poorly adapted to recognize and manage relationships between the various components of the network. A conventional network might, for example, represent a user by copying all of the phone data and all of the phone mail data for the person to a distinct user entity. It will be appreciated that such an approach contemplates a significant and undesirable duplication of data. In addition, the traditional approach to managing communication networks frequently lacks sufficient flexibility to smoothly integrate new products or components into the network. Systems designed around a finite number of defined component types must typically undergo substantial revision to encompass a new product thereby slowing the introduction of new features and raising the cost of maintaining the network. Therefore it would be highly desirable to implement a communication network with improved performance

and flexibility. It would be still further desirable if the implemented solution utilized existing protocols and architectures to the extent possible and took advantage of relationships between various components to model network features in an efficient manner.

5

SUMMARY OF THE INVENTION

Broadly speaking, the present invention contemplates a
10 communication network and an associated network manager server. The network includes one or more instances of a first object type and one or more instances of a second object type. The first object type is associated with a first product of the communication network and the second object type is associated with a second product of the network. The network includes a first
15 local module or other means for configuring each instance of the first object type and a second local module for configuring each instance of the second object type. A network management server of the network includes a product specific coordinator. The product specific coordinator includes means for coordinating configuration activities among each instance of the first object
20 type via the first local module and means for coordinating configuration activities among each instance of the second object type via the second local module. The network further includes a network coordinator adapted for configuring each instance of a network object. The network object includes a first component associated with the first object type and a second component
25 associated with the second object type. A suitable network object might include, as an example, a person object that includes a PBX component and a phone mail component. The communication network further includes a network management client that includes a graphical user interface adapted for enabling a user to invoke the network management server.

30

In one embodiment, the first object type is a phone mail object and the first local module comprises a phone mail server process while the second object type is a PBX object and the second local means comprises a PBX server process. In the preferred embodiment, the communication network of

claim includes a CORBA compliant interface between the product specific coordinator and the first local module. The network coordinator is preferably adapted for accessing network object data from an LDAP compliant directory server. The network preferably further includes a first LDAP compliant bridge for uploading first object type data from each instance of the first object type to the directory server and a second LDAP compliant bridge application for uploading second object type data from each instance of the second object type to the directory server.

The invention further contemplates a method of managing a communication network. The method includes identifying the components of a network object in response to a network configuration request. A first local configuration module or application is then invoked to configure a first component of the network object and a second local configuration application invoked to configure a second component of the network object. The step of identifying the components is preferably accomplished by accessing object data from an LDAP compliant directory server. The configuring of the first component comprises is accomplished in one embodiment by configuring a PBX object of the communication network and includes taking an action such as removing, adding, and changing the first component while the configuring of the second component comprises configuring a phone mail object of the communication network.

BRIEF DESCRIPTION OF THE DRAWINGS

A better understanding of the invention is obtained when the following detailed description is considered in conjunction with the following drawings in which:

Fig. 1 is a simplified block diagram of a communication network according to one embodiment of the invention;

Fig. 2 is a simplified representation of a network management client according the one embodiment of the invention;

Fig. 3 is a simplified representation of one embodiment of a product specific coordinator of a network management server according to the invention;

Fig. 4 is a hierarchical diagram of various objects of the invention;

Fig. 5 is a diagram of a person object according to one embodiment of the invention; and

Fig. 6 is a representation of an embodiment of the network manager server of the invention emphasizing a directory server network database structure.

DETAILED DESCRIPTION OF THE INVENTION

Referring to FIG. 1, an exemplary embodiment of a communication network according to the present invention is generally identified with by reference numeral **100**. Communication network **100** preferably includes one or more communication devices or product types including, as examples, PBX's and phone mail systems. Each product type within communication network **100** is represented or modeled in software by an object type as will be familiar to those skilled in the field of object oriented programming languages. As depicted in Fig. 1, network **100** includes one or multiple instances of a first object type **122a...122m** (generically or collectively referred to as first object type **122**) and one or multiple instances of a second object type **124a...124k** (generically or collectively referred to as second object type **124**). Local configuration software for each product type provides the means for administering each instance of the corresponding product type. Exemplary local configuration software is the LC Win software available from Siemens Corp. Accordingly, computer system **100** as depicted in Fig. 1 includes first local configuration software **120a** and second local configuration software **120b**. Additional instances of local configuration software maybe included for each additional communication product included in network **100**.

The services for administering the different products comprising communication system **100** are used or invoked by network management server **102**. Network management server (NMS) **102** provides the core
 5 functionality for the network management-configuration module (NMC) **101**. NMC **101** enables a user to control all network and local configuration activities from a single point of entry. NMS **102** preferably includes a configuration model of network **100** embedded with information sufficient to enable NMS **102** to administer the entire domain. NMS **102** provides the
 10 framework for configuration of all supported product types. As indicated in Fig. 1, NMS **102** is comprised of two major layers, namely, a product specific coordinator **106** and a network coordinator **104**. Product specific coordinator **106** is adapted for coordinating configuration activities between different instances of a specified product line within a domain. As an example, the
 15 detailed coordination of moving a phone within a PBX or from one PBX to another is handled by a product specific PBX coordinator. Product specific coordinator **106** comprises a set of modules **108a**, **108b**... (collectively referred to as modules **108**) corresponding to each product type within network **100**. The set of modules **108** provide means for invoking or using the
 20 operations supplied by corresponding instances of local configuration modules **120**. In other words, product specific coordinator **106** is the client for local configuration modules **120**.

Referring briefly to Fig. 3, an embodiment of product specific
 25 coordinator **106** is presented including a first product specific module **108a** adapted for accessing the functionality of a first local configuration module **120a** and a second product specific module **108b** adapted for invoking a second local configuration module **120b**. Product specific modules **108** may utilize a proprietary application programming interface (API) or a standard
 30 interface such as a common object request broker architecture (CORBA) compliant interface definition language (IDL) to communicate with their corresponding local configuration modules **120**. For the example depicted in Fig. 3, first product specific module **108a** invokes first local configuration

module **120a** using API **134** while second product specific module **108b** communicates with second local configuration module **120b** via CORBA IDL **136**.

5

Returning now to Fig. 1, network coordinator **104** is adapted for coordinating configuration activities across different product types while using product specific coordinator **106** to handle specific information relating to each managed product. Network coordinator **104** is primarily responsible for managing network objects including objects comprised of two or more product components. In the context of communication network **100**, for example, a network object in the form of a person object might comprise a phone (that is part of a PBX object) and a phone mail box that is part of a phone mail object. Network coordinator **104** is designed to ensure that each of the components of the network object are properly accounted for when a network object is managed. If, as an example, a person object is deleted from the domain managed by NMC **101**, network coordinator **104** insures that all components of the person object in all nodes within the domain are removed.

The removal of a person object from network **100** in one embodiment would be accomplished as follows. Network coordinator **104** would first identify the components of the person object. Upon identifying a phone component that is part of a PBX object, network coordinator will initiate a "delete" operation to a PBX module identified for purposes of this example as first product specific module **108a** of product specific coordinator **106**. PBX module **108a** then proceeds with the delete request from network coordinator **104** by invoking an API or CORBA IDL interface to the corresponding PBX local configuration module identified for purposes of this example by first local configuration module **120a**. PBX module **108a** will then update all dial plans for all PBX units **122** within the network domain after receiving confirmation from PBX local configuration module **120a** that the delete request was completed successfully. When PBX module **108a** has completed its update, network coordinator **104** will identify the phone mail component of the person

object and proceed with a delete procedure by issuing a delete operation to a phone mail module identified for purposes of this example as second product specific module **108b**. Phone mail module **108b** will then invoke its

5 corresponding local configuration module **120b** to delete the appropriate phone mail box from network **100**. Phone mail local configuration module **120b** will then inform network coordinator **104** when it has completed the requested operation.

10 Network management server **102** is invoked in the preferred embodiment through network management client **110**. Referring to Fig. 2, the depicted embodiment of network management client **110** includes two primary layers, namely, graphical user interface layer **130** and a proprietary API layer **132**. The GUI layer **130** is adapted to handle manipulation of a

15 display screen to provide a user of NMC **101** with a useable interface for invoking operations and requests to NMS **102**. API layer **132** is configured to pack and unpack NMC commands between GUI layer **130** and NMS **102**. Communication between network management client **110** and NMS **102** is preferably achieved using meta-data based commands for carrying object

20 data between network management client **110** and NMS **102**. In an alternative embodiment, a CORBA compliant object request broker (ORB) will be used to handle requests between NM Client **110** and NM server **102** in lieu of API layer **132**.

25 In the preferred embodiment of NMC **101**, all administrative entities in the managed network or domain are referred to as network managed objects. A network managed object is defined for purposes of this invention as an entry with a unique identification on which administrative actions such as, add, move, delete, and query can be performed. As diagrammed in Fig.

30 4, the preferred embodiment of NMC **101** contemplates two categories of network managed objects, network entry objects and product entry objects **150**. Each network entry object **140** is a representation of a composite object that includes components residing in one or more nodes of the domain. In

the preferred embodiment, network entry objects **140** retrieve their data from a directory server type application. Object data for network entry objects **140** is comprised of relevant data from all the components that make up network entry object **140**. Network entry objects **140** capture the relationship between the various local components. A first type of network entry object is a person object **141** referred to previously. Person object **141** preferably includes multiple components from various communication product types. As an example, a first component of person object **141** as depicted in Fig. 5 may be a phone **163** associated with a PBX object type **161** while a second component may comprise a phone mail box associated with a phone mail object **162**. Additional components (not depicted in Fig. 5) of person object **141** may includes a CCMS agent with an agent identification or an IP address for an internet voice phone application. A network entry object **140** requires at least one component residing in one of the network systems or nodes, but it is not strictly required that each example of network entry object **140** include a component associated with each product type. Returning to Fig. 4, a second type of network entry object **140** is represented by resource object **142**. An example of a resource object **142** is the trunk object represented in Fig. 4 by reference numeral **143**. A trunk resource suitable for connecting two PBX systems is modeled in NMC **101** as a pair of end points residing in the respective PBX systems connected by the trunk. NM server **102** is adapted to configure trunk object **143** by configuring the two trunk resource end points. Trunk object **143** may be reconfigured, as an example, by moving one of the trunk resource end points to a different PBX system. Another example of a network resource is a bus connecting a system on which a phone mail server process resides and a PBX system. Similar to the trunk resource, a model of this bus resource includes the pair of end point addresses corresponding to the phone mail system and the PBX system respectively. In the preferred embodiment, resource objects will retrieve their data from a directory server application and will each have a unique identification from the directory server and the components that comprise the resource object will include the addresses of the end points that define the resource object.

Fig. 4 further depicts a product entry object represented by reference numeral **150**. Each product entry object **150** is a representation of a local object managed by NMC **101**. Each product entry object can be presented as a component to a network entry object **140** such as when, for example, a phone object is presented to a person object. In the preferred embodiment, relevant product entry object data will be uploaded to a directory server application as a component of the network entry object data. Suitable product entry objects for a phone mail system could include, for example, a mail box profile object and a class of service object. While some product entry objects **150** comprise a component of a corresponding network entry object **140**, it is preferably not required that each product entry object **150** be a component of a network entry object **140**. A peripheral board of a PBX system, for example, might comprise a product entry object not associated with any corresponding network entry object.

In suitable embodiments, NMC **101** might include one or more of a number of support objects (not explicitly depicted in the drawings) as described herein to provide functions for NMS **102** to process requests from network manager client **110**. A front end object is adapted to receive and re-distribute NMC commands from network manager client **110** to other objects of NMS **102**. The front end object can serve as the entry point for NMC requests from network manager client **110** to NMS **102**. A network object handler is adapted to track which network entry objects **140** have been created and to ensure that only one instance of a network entry object **140** is created per execution thread. In the preferred embodiment, network manager client **102** will utilize multithreaded processing. Each execution thread will support a session with one network manager client **110**. In the presently preferred embodiment, 15 (or fewer) execution threads (i.e., clients) can be supported by each NMS **102**. The network object handler ensures that only one instance of a network entry object **140** is created per execution thread. In one embodiment, verifying the uniqueness of each network entry object **140** is accomplished by establishing a network entry object identification for

each newly created network entry object **140** and maintaining the identifications on a directory server. The network object handler uses the network entry object identifications to ensure that each network entry object is unique. In addition to network object handler, each product managed by NMC **101** will include its own product object handler. Examples of such product handlers for communication network **100** include a PBX object handler, a phone mail object handler, and a telephony internet service. Similar to the network object handler, the product object handler will track instances of product entry objects **150**. In one embodiment, the product entry object identifications will include an internal, product specific identification in combination with a system / node identification. A PBX entry object, as an example, might include in its product entry object identification a PBX identification, a phone product identification, and a station number. The product entry object handler will ensure the all non-static objects are removed after completion of a configuration request. Additional examples of support objects in NMC **101** may include an LDAP interface object that includes all LDAP specific details for accessing a directory server application and an administration object that facilitates, as examples, saving and getting customer template files, issuing requests for full or partial uploads from individual products, and uploading and download batch files.

With reference again to Fig. 1, one embodiment of communication network **100** as indicated above, will include a directory server **200**. The use of directory server **200** frees NMC **101** to function without requiring a complete upload of the database of each system being managed by NMC **101**. Instead, NMS **102** requires only a subset of database information sufficient to determine the location of each object within the domain. An exemplary directory server application includes Directory Server 3.0 (or later) from Netscape Communications Corporation, Mountain View, CA. In one embodiment, each product managed by NMC **101** will include its own bridge suitable for uploading data to directory server **200**. In the preferred embodiment, directory server **200** and each bridge application are LDAP

compliant. The bridge applications are adapted for retrieving data from their respective systems and updating directory server **200**.

5 Directory server **200** will be organized according to the configuration model of NMC **101**. In the example presented earlier in which a person object includes a PBX object and a phone mail object, relevant PBX object data is transferred to directory server **200** via a PBX bridge application. The data uploaded to directory server **200** may include, as examples, a PBX
10 identifier, a voice station number, a port equipment number, a data station number, a phone type, location code, the person's name, and the person's department name. Similarly, a phone mail bridge application uploads relevant information to directory server **200** including the phone mail system identifier, a mail box name, and an extension number. The records for each person
15 may be stored under the person's name and department name such that the person may be located by either one. Fig. 6 is a conceptualized diagram of communication network **100** emphasizing the relationship between the individual product databases indicated by reference numerals **210a**, **210b**, and **210c** and the network database **212**. Each product uploads data from its
20 corresponding product database **210** to network database **212** via a corresponding bridge application **214**. For example, PBX data is uploaded from PBX database **210a** to network database **212** via PBX bridge application **214a**. In the depicted embodiment, The PBX data **216a** uploaded to network database **212** comprises only the portion of PBX database **210a** necessary to
25 enable NMS **102** to be able to locate the appropriate data. Each bridge application **214** is adapted to fully or partially upload relevant data from local configuration management software and to regularly the network database with new data at a frequency defined by NMC **101**. In addition to person objects, network managed objects in the preferred embodiment may include
30 node type objects. Systems and nodes in the managed domain are identified in the preferred embodiment as network entry objects **140**. The physical or logical relationships between the systems and nodes of the network **100** are specified by users when the system or node is created in the domain and

(5)

WHAT IS CLAIMED IS:

- 1 1. A communication network, comprising:
2 at least one instance of a first object type associated with a first product of the
3 communication network;
4 at least one instance of a second object type associated with a second
5 product of the communication network;
6 first local means for configuring each instance of the first object type;
7 second local means for configuring each instance of the second object
8 type;
9 a network management server comprising a product specific
10 coordinator including means for coordinating configuration activities among
11 each instance of the first object type via the first local means and means for
12 coordinating configuration activities among each instance of the second
13 object type via the second local means and further comprising a network
14 coordinator adapted for configuring each instance of a network object
15 comprising a first component associated with the first object type and a
16 second component associated with the second object type; and
17 a network management client including a graphical user interface
18 adapted for enabling a user to invoke the network management server.

- 1 2. The communication network of claim 1, wherein the first object type
2 comprises a phone mail object and the first local means comprises a phone
3 mail server process.

- 1 3. The communication network of claim 1, wherein the second object type
2 comprises a PBX object and the second local means comprises a PBX server
3 process.

- 1 4. The communication network of claim 1, further comprising a CORBA
2 compliant interface between the product specific coordinator and the first local
3 means.

- 1 5. The communication network of claim 1, wherein the network
2 coordinator includes means for accessing network object data from a
3 directory server.
- 1 6. The communication network of claim 5, wherein the directory server is
2 LDAP compliant.
- 3 7. The communication network of claim 5, further comprising a first LDAP
4 compliant bridge for uploading first object type data from each instance of the
5 first object type to the directory server and a second LDAP compliant bridge
6 application for uploading second object type data from each instance of the
7 second object type to the directory server.
- 1 8. The communication network of claim 1, wherein the network
2 management client includes a CORBA compliant interface to the network
3 management server.
- 1 9. The communication network of claim 1, wherein the network object is a
2 person object comprising a phone mail object component and a PBX object
3 component.
- 1 10. The communication network of claim 1, wherein the network object
2 comprises a resource object including a first end point address and a second
3 end point address.
- 1 11. The communication network of claim 10, wherein the first and second
2 end point addresses reside in different instances of the first object type.
- 1 12. The communication network of claim 10, wherein the first end point
2 address resides in an instance of the first object type and the second end
3 point address resides in an instance of the second object type.

1 13. A communication network manager, comprising:
2 a network management server including a product specific coordinator
3 comprising means for coordinating configuration activities among each
4 instance of a first object type via first local configuration means and means for
5 coordinating configuration activities among each instance of a second object
6 type via second local means, and further comprising a network coordinator
7 adapted for configuring each instance of a network object comprising a first
8 component associated with the first object type and a second component
9 associated with the second object type; and
10 a network management client suitable for enabling a user to invoke the
11 network management server.

1 14. The network manager of claim 13, wherein the first object type
2 comprises a phone mail object and the first local means comprises a phone
3 mail server process.

1 15. The network manager of claim 13, wherein the second object type
2 comprises a PBX object and the second local means comprises a PBX server
3 process.

1 16. The network manager of claim 13, further comprising a CORBA
2 compliant interface between the product specific coordinator and the first local
3 means.

1 17. The network manager of claim 13, wherein the network coordinator
2 includes means for accessing network object data from a directory server.

1 18. The network manager of claim 17, wherein the directory server is
2 LDAP compliant.

1 19. The network manager of claim 17, further comprising a first LDAP
2 compliant bridge for uploading first object type data from each instance of the
3 first object type to the directory server and a second LDAP compliant bridge
4 application for uploading second object type data from each instance of the
5 second object type to the directory server.

1 20. The network manager of claim 13, wherein the network object is a
2 person object comprising a phone mail object component and a PBX object
3 component.

1 21. The network manager of claim 13, wherein the network object
2 comprises a resource object including a first end point address and a second
3 end point address.

1 22. The network manager of claim 21, wherein the first and second end
2 point addresses reside in different instances of the first object type.

1 23. The network manager of claim 21, wherein the first end point address
2 resides in an instance of the first object type and the second end point
3 address resides in an instance of the second object type.

1 24. A method of managing a communication network, comprising:
2 identifying the components of a network object in response to a
3 network configuration request;
4 invoking a first local configuration application to configure a first
5 component of the network object; and
6 invoking a second local configuration application to configure a second
7 component of the network object.

- 1 25. The method of claim 24, wherein the step of identifying the
2 components comprises accessing object data from an LDAP compliant
3 directory server.
- 1 26. The method of claim 24, wherein the configuring of the first component
2 comprises configuring a PBX object of the communication network.
- 1 27. The method of claim 26, wherein the step of configuring the first
2 component comprises taking an action selected from the group comprising
3 removing, adding, and changing the first component.
- 1 28. The method of claim 24, wherein the configuring of the second
2 component comprises configuring a phone mail object of the communication
3 network.
- 1 29. The method of claim 28, wherein the step of configuring the second
2 component comprises taking an action selected from the group comprising
3 removing, adding, and changing the second component.
4

ABSTRACT OF THE DISCLOSURE

A communication network and an associated network manager server according to the invention includes one or more instances of a first object type and one or more instances of a second object type. The first object type is associated with a first product of the communication network such as a PBX and the second object type is associated with a second product of the network such as a phone mail product. The network includes a first local module for configuring each instance of the first object type and a second local module for configuring each instance of the second object type. A network management server of the network includes a product specific coordinator. The product specific coordinator includes means for coordinating configuration activities among each instance of the first object type via the first local module and means for coordinating configuration activities among each instance of the second object type via the second local module. The network further includes a network coordinator adapted for configuring each instance of a network object, such as a person object that includes a PBX component and a phone mail component. The network object includes a first component associated with the first object type and a second component associated with the second object type. The communication network further includes a network management client that includes a graphical user interface adapted for enabling a user to invoke the network management server.




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6

DECLARATION FOR PATENT APPLICATION & POWER OF ATTORNEY

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

COMMUNICATION NETWORK MANAGEMENT

the specification of which (check one)

X is attached hereto.

___ was filed on _____ as Application Serial No.

and was amended on _____ (if applicable)

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose all information known to me to be material to patentability as defined in Title 37, Code of Federal Regulations § 1.56.

I hereby claim foreign priority benefits under Title 35, United States Codes, § 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

PRIOR FOREIGN APPLICATION(S)

Priority claimed

(Number)	(Country)	(Day/month/year filed)	Yes	No
(Number)	(Country)	(Day/month/year filed)	Yes	No
(Number)	(Country)	(Day/month/year filed)	Yes	No

I hereby claim the benefits under Title 35, United States Code, § 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, § 1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

(Application Serial No.)	(Filing date)	(Status)
		(patented,pending,abandoned)

(Application Serial No.)	(Filing date)	(Status)
		(patented,pending,abandoned)

Power of Attorney: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. (list name and registration number)

Adel A. Ahmed, Reg. No. 29,606; Stanton C. Braden, Reg. No. 32,556; Robert T. Canavan, Reg. No. 37,592; Dexter K. Chin, Reg. No. 38,842; Joseph S. Codispoti, Reg. No. 31,819; Lawrence C. Edelman, Reg. No. 29,299; Andreas Grubert, Limited Recognition Under 37 CFR §10.9(b); Mark H. Jay, Reg. No. 27,507; Rosa S. Kim, Reg. No. 39,728; David W. Laub, Reg. No. 38,708; Peter A. Luccarelli, Jr., Reg. No. 29,750; Jeffrey P. Morris, Reg. No. 25,307; Donald B. Paschburg, Reg. No. 33,753; Jeffrey Slusher, Reg. No. 34,729; Darryl A. Smith, Reg. No. 37,723; Heather S. Vance, Reg. No. 39,033; Scott T. Weingaertner, Reg. No. 37,756; Robert A. Whitman, Reg. No. 36,966; and Ira Lee Zebrak, Reg. No. 31,147.

Send correspondence to:

Siemens Corporation
Intellectual Property Department
186 Wood Avenue South
Iselin, N.J. 08830

Direct telephone calls to:

Elsa Keller
Legal Administrator (908) 321-3026

I hereby declare that all statements made herein on my own knowledge are true and that all statements made on information and belief are believed to be true, and further that these statements were made with the knowledge that willful false

Full name of first
joint inventor:

Chickens

Aug 23 / 1999

San Jose, California

Canada

3694 Lynx Drive, San Jose, CA ~~95036~~ 95120 (TT)

Hung B. Nguyen

Hunzbad Nguyen

8/23/99

Milpitas, California

U.S.A.

2239 Wellington Drive, Milpitas, CA 95035

Frederick Kull

Frederick M. Hill for

8/23/99

Campbell, California

U.S.A.

695 Cypress Lane, Campbell, CA 95008